This is a free page sample. Access the full version online.

Under Revision see DR 85292
" " " DR 85293

SUPERSEDED BY AS 1788.1 - 1987 and AS 1788.2 - 1987 ~~Project Terminated Aug 1987~~

AS 1788—1975
UDC 621.924—783

Australian Standard 1788—1975

ENDORSED BY SAMZ Annual List 1980

SUPERSEDED BY 1788.1 + 1788.2 of 1987 - Jan/Feb 1989

SAA ABRASIVE WHEELS SAFETY CODE

METRIC UNITS

STANDARDS ASSOCIATION OF AUSTRALIA

Incorporated by Royal Charter

STANDARDS ASSOCIATION OF AUSTRALIA SYDNEY LIBRARY

8

This is a free page sample. Access the full version online.

THE FOLLOWING SCIENTIFIC, INDUSTRIAL AND GOVERNMENTAL ORGANIZATIONS and departments were officially represented on the committee entrusted with the preparation of this standard:

Associated Chambers of Manufactures of Australia

Department of Labor and Immigration

Department of Defence

Departments of Labour and Industry

National Safety Council of Australia

Railways of Australia Committee

Safety Engineering Society of Australasia

This standard, prepared by Committee SF/12, Abrasive Wheels (Safety), was approved on behalf of the Council of the Standards Association of Australia on 2 May 1975, and was published on 1 December I975.

To keep abreast of progress in industry, Australian standards are regularly reviewed. Suggestions for improvements to published standards, addressed to the headquarters of the Association, are welcomed.

This is a free page sample. Access the full version online.

AUSTRALIAN STANDARD

CODE OF PRACTICE FOR
THE USE, CARE AND GUARDING OF ABRASIVE WHEELS

known as the

SAA ABRASIVE WHEELS SAFETY CODE

AS 1788—1975

First published (as AS CZ12) 1965
Revised and issued as AS 1788 1975

PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY (Copyright)

STANDARDS ASSOCIATION OF AUSTRALIA
SYDNEY LIBRARY

ISBN 0 7262 0633 4

28 NOV 1975

This is a free page sample. Access the full version online.

PREFACE

This code was prepared by the Association's Committee on Abrasive Wheels (Safety) as a revision and metrication of AS CZ12—1965, which it accordingly supersedes.

The code is based on the corresponding American standard, ANSI* B7.1—1970, and the committee has considered amendments which had been incorporated in that code.

Wheel speed is now expressed in revolutions per minute with surface speed being expressed in metres per second.

Some figures have been replaced by more suitable photographs which better illustrate the principles of guarding.

* American National Standards Institute.

CONTENTS

		Page
FOREWORD		4
SECTIONS		
1	Scope and Definitions	4
2	Handling, Storage and Inspection of Wheels	11
3	General Machine Conditions	13
4	Guards	18
5	Flanges	25
6	Mounting	28
7	Speeds	31
8	Special Speeds	33
9	General Operating Rules	35
10	Mounted Wheels	37
TABLES		
1	Minimum Diameters of Machine Spindles	14
2	Minimum Thickness of Machine Face Plates for Mounting Abrasive Discs	15
3	Minimum Thickness of Machine Face Plates for Machines Using Plate Mounted Wheels	17
4	Minimum Thickness of Peripheral and Side Members for Guards for Abrasive Wheels Running at Speeds not exceeding 81 m/s	21
5	Minimum Thickness of Peripheral and Side Members for Guards for Cutting-off Wheels	22
6	Guide for Construction of Drawn Steel Guards for Wheels 50 mm Thick and less than 250 mm in Diameter	22
7	Drawn Steel Guard for Portable Grinders Using Types 27 and 28 Wheels at Speeds up to 72 m/s	23
8	Wheel Exposure for Band Type Guards	23
9	Guide for Construction of Band Type Guards	23
10	Minimum Dimensions for Straight Relieved Flanges	26
11	Minimum Dimensions for Straight Unrelieved Flanges for Wheels with Threaded Inserts	26
12	Minimum Dimensions for Straight Adaptor Flange — for Organic Bonded Wheels over 32 mm Thick	27
13	Minimum Dimensions for Straight Flanges Used as Wheel Sleeves for Precision Grinding	27
14	Standard Maximum Speeds	32
15	Wheel Manufacturers' Testing Speeds	31
16	Special Maximum Operating Speeds for Mounted Wheels	37
17-25	Maximum Operating Speeds for Mounted Wheels	38-50
FIGURES		
1	Grinding Face	4
2	Reinforced Organic Bonded Wheel	5
3	Typical Reducing Bushing	5
4	Typical Through-feed Centreless Grinding Operation	5
5	Internal Grinding	5
6	Off-hand Grinding	6
7	Portable Grinding Using a Cup Wheel	6
8	Coping Using a Reinforced Organic Bonded Wheel	6
9	Cutting Off	6
10	Type 1—Straight Wheel	6
11	Type 2—Cylinder Wheel	7
12	Typical Abrasive Discs	7
13	Type 4—Taper-sided Wheel	7
14	Type 5—Recessed-one-side Wheel	7
15	Type 7—Double Recessed Wheel	7
16	Type 6—Straight Cup Wheel	7
17	Type 11—Flaring Cup Wheel	8
18	Type 12—Dish Wheel	8
19	Type 13—Saucer Wheel	8
20	Cone and Plug Wheels	8
21	Relieved and/or Recessed Wheels	9
22	Depressed Centre Wheel (Flat Rim)	10
23	Typical Mounted Wheels	10
24	Threaded Hole Wheels	10
25	A Well-designed Grinding Wheel Storage Area Used by a Large Industrial Plant	11

This is a free page sample. Access the full version online.

		Page
26	A Rack Design Suitable for Handling of a Wide Variety of Abrasive Wheels	12
27	Ring Test	12
28	Machine Spindle Thread	13
29	Mounting of Threaded Hole Wheel	15
30	Unrelieved and Relieved Flange	15
31	Inserted Nut Mounting	16
32	Inserted Nut Type Abrasive Disc	16
33	Inserted Washer Type Abrasive Disc	16
34	Method of Mounting Abrasive Discs	16
35	Plate Mounted Type Wheels	17
36	Resinoid Bonded Flaring Cup Wheel	18
37	Unthreaded Hole Cup Wheel and Revolving Cup Guard Assembly	18
38	90° Maximum Exposure (Bench and Floor Stands)	18
39	125° Maximum Exposure (Bench and Floor Stands)	18
40	Well-designed Guard for Bench Grinder	19
41	Well-designed Fabricated Guard on a Floor Stand Grinder	19
42	180° Maximum Exposure (Cylindrical Grinder)	19
43	Cylindrical Grinding Machine Employing Well-designed Wheel Guard	19
44	150° Maximum Exposure (Cutting-off Machines and Surface Grinders)	19
45	Surface Grinder with Well-designed Guard Conforming to Basic Requirements	19
46	180° Maximum Exposure (Swing Frame Grinder)	20
47	Swing Frame Grinder with Guard Enclosing at least 180° of Wheel	20
48	60° Maximum Exposure (Top Grinding)	20
49	Wheel Properly Mounted and Guarded on a Right Angle Portable Grinder	20
50	Correct Exposure Adjustment	20
51	Correct Exposure Adjustment	20
52	Incorrect Exposure Adjustment	20
53	Typical Fabricated Guard	21
54	Cutting-off Machine Having Wheel Larger than 400 mm Diameter	22
55	Typical Drawn Steel Guard for Wheels 250 mm Diameter and Smaller	22
56	Details for Guard for Thin Abrasive Wheels	23
57	Typical Application of Drawn Steel Guard	23
58	Details for Band Type Guard	23
59	Properly Constructed Band Type Guard	24
60	Flanges at least One-third Diameter of Wheel	25
61	Correct and Incorrect Methods of Mounting Wheels Having Small Holes	25
62	Correct and Incorrect Methods of Mounting Wheels Having Large Holes	25
63	Straight Relieved Flange—Driving Flange Secured to Spindle	26
64	Straight Unrelieved Flange—Driving Flange Secured to Spindle	26
65	Straight Adaptor Flange	27
66	Method of Checking Flange with Straightedge	27
67	Straight Flanges used as Wheel Sleeves—Driving Flange Secured to Spindle	27
68	Blotter Shown Between Abrasive Wheel and Flange	28
69	Result when Spindle End Nut is Excessively Tightened	28
70	Depressed Centre Wheel Mounting	29
71	Mounting of a Segmental Wheel Assembly	30
72	Dressing a Wheel	35
73	Sketch of Floor Stand Grinder showing Adjustment of Work Rest to Wheel	36
74	Sketches Defining Overhang Dimensions "O"	37

APPENDICES

A	Sample Report Form for Abrasive Wheel Breakages	51
B	Conversion Table for Wheel Speeds	54

SAI GLOBAL

This is a free preview. Purchase the entire publication at the link below:

Product Page

Looking for additional Standards? Visit Intertek Inform Infostore

Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation