Australian Technical Specification

Meters for non-urban water supply

Part 2: Specification for closed conduit meters fully charged



This is a free page sample. Access the full version online.

This Australian Technical Specification was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed. It was approved on behalf of the Council of Standards Australia on 6 May 2008.

This Technical Specification was published on 30 June 2008.

The following are represented on Committee CE-024:

- Australian Industry Group
- Department of Natural Resources and Water, Qld
- Institute of Instrumentation, Control and Automation Australia
- Irrigation Australia
- National Measurement Institute
- NSW Department of Commerce
- University of South Australia
- Water and Wastewater Association of Australia

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Technical Specification through their representation on the Committee.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting **www.standards.org.au**

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at **mail@standards.org.au**, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Technical Specification

Meters for non-urban water supply

Part 2: Specification for closed conduit meters fully charged

First published as ATS 4747.2-2008.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia ISBN 0 7337 8755 X

PREFACE

This Australian Technical Specification was prepared by the Standards Australia Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits.

The objective of this Australian Technical Specification is to provide manufacturers with requirements for irrigation and non-urban water meters to meet the requirements of the National Water Initiative Clause 88.

It should be noted that NMI M 10-1 *Metrological and technical requirements* specifies the metrological and technical requirements for pattern approval and verification of water meters to comply with the National Measurement Regulation. Where appropriate, the requirements of this Australian Technical Specification are sourced from NMI M 10-1, *Metrological and technical requirements*, and NMI M 10-2, *Test methods*, both of which take precedence over the metrological requirements of this Australian Technical Specification.

This Australian Technical Specification includes essential requirements to maintain progress with technology in the water meter industry.

This document is part of a suite of Australian Technical Specifications covering the metering of non-urban water supply, as follows:

ATS	
-----	--

4747	Meters	for non-urban water supply
4747.1	Part 1:	Glossary of Terms
4747.2	Part 2:	Specification for closed conduit meters fully charged
4747.3	Part 3:	Specification for open channel meters
4747.5	Part 5:	Installation and commissioning of closed conduit meters fully charged
4747.6	Part 6:	Installation and commissioning of open channel meters
4747.8	Part 8:	In-service compliance for closed conduit meters fully charged
4747.9	Part 9:	In-service compliance for open channel meters

The ATS 4747 suite is being published in the first instance as Australian Technical Specifications. Following a period of trial and review of no more than 2 years it is intended to republish it as an Australian Standard.

The terms 'normative' and 'informative' have been used in this Australian Technical Specification to define the application of the Appendix to which they apply. A 'normative' Appendix is an integral part of an Australian Technical Specification. An 'informative' Appendix is for information and guidance only.

Page

SECTIO	N 1 SCOPE AND GENERAL	
1.1	SCOPE	5
1.2	APPLICATION	
1.3	NORMATIVE REFERENCES	6
1.4	DEFINITIONS	
1.5	PREFERRED UNITS	
110		•• •
SECTIO	N 2 MATERIALS	
2.1	GENERAL	8
2.2	RESISTANCE TO CORROSION	
SECTIO	N 3 DESIGN	
3.1	DIMENSIONS AND CONNECTIONS	9
3.2	SELF-CONTAINED METERS	9
3.3	FLOW COMPUTER	9
3.4	ZERO FLOW CONDITIONS	10
3.5	METER DISPLAY	10
3.6	CALIBRATION ADJUSTMENT DEVICE	
3.7	OUTPUT	
3.8	ELECTRONIC STORAGE	
3.9	FREQUENCY OF MEASUREMENT	
3.10	WATER METERS EQUIPPED WITH ELECTRONIC DEVICES	
3.11	PROTECTIVE DEVICES	
	FROST PROTECTION	
	ELECTRONIC SEALING DEVICES	
	ENVIRONMENTAL REQUIREMENTS	
	ENVIRONMENTAL REQUIREMENTS	
5.15	ENCLOSURE	19
SECTIO	N 4 PERFORMANCE REQUIREMENTS	
4.1	GENERAL	20
4.2	MEASUREMENT PERFORMANCE	
4.2	PRESSURE LOSS	
4.3	OPERATING TEMPERATURE	
4.4	ULTRAVIOLET LIGHT EXPOSURE	
4.5	ELECTROMAGNETIC SUSCEPTIBILITY	
4.7	TORQUE RESISTANCE OF THREADED END CONNECTIONS	
4.8	WATERTIGHTNESS	
4.9	REVERSE FLOW	
	LEAKAGE	
	ENDURANCE	24
4.12	PERFORMANCE TESTS FOR WATER METERS WITH ELECTRONIC	~ (
	DEVICES	24
OF OTIO		
	N 5 MARKING AND PRODUCT DOCUMENTATION	•
5.1	IDENTIFICATION MARKS	
5.2	VERIFICATION MARKS	
5.3	PRODUCT DOCUMENTATION	
	INSTALLATION INSTRUCTIONS	
5.5	COMMISSIONING INSTRUCTIONS	27



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation