

AS/NZS 1254:2002

AS/NZS 1254

Australian/New Zealand Standard™

**PVC pipes and fittings for stormwater
and surface water applications**

AS/NZS 1254:2002

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee PL/21, Unplasticised PVC Pipes. It was approved on behalf of the Council of Standards Australia on 14th June, 2002 and on behalf of the Council of Standards New Zealand on 23 May 2002. It was published on 10 July 2002.

The following are represented on Committee PL/21:

Australian Gas Association
Australian Nuclear Science and Technology Organisation
CSIRO Building, Construction and Engineering
Certification Bodies (Australia)
Institution of Engineers Australia
Local Government New Zealand
Master Plumbers Australia
Master Plumbers, Gasfitters and Drainlayers New Zealand
New Zealand Water and Waste Association
PVC Pipelines Industry Association of Australasia
Plastics Institute of New Zealand
Plastics and Chemicals Industries Association
Water Services Association of Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

AS/NZS 1254:2002

Australian/New Zealand Standard™

PVC pipes and fittings for stormwater and surface water applications

Originated in Australia as AS 1254—1973.
Previous edition AS 1254—1991.
Originated in New Zealand as NZS 7649—1974.
Previous New Zealand edition NZS 7649:1988.
AS 154—1991 and NZS 7649—1988 jointly revised and
redesignated AS/NZS 1254:2002.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001
and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 4484 2

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee PL-021, PVC, ABS and Polyamide Pipe Systems, to supersede AS 1254—1991, *Unplasticized PVC (UPVC) pipes and fittings for storm and surface water applications*, and NZS 7649—1988, *Unplasticized PVC sewer and drain pipe and fittings*.

The objective of this Standard is to outline minimum requirements for the manufacture and performance of PVC pipes and fittings for stormwater applications for use by manufacturers, specifiers and purchasers of such products.

For pipe of nominal diameter DN 75 there is one classification based on minimum wall thickness. This is class SN2. For pipe of nominal diameter DN 90 and DN 100 there are three classifications based on minimum pipe stiffness. These are pipe stiffness classes SN2, SN4 and SN8. For pipes greater than DN 100 there are 4 stiffness classes, SN1.5, SN2, SN4 and SN8.

In general, pipes manufactured to AS 1254 — 1991 have been replaced by a minimum pipe stiffness requirement of SN2 and pipes manufactured to NZS 7649:1988 have been replaced by a minimum pipe stiffness requirement of SN4. Sufficient dimensional information is provided to ensure compatible joints, minimum bore and resistance to abrasion.

Stiffness class SN8 has been included for applications where heavy loads, for example deeper burial, traffic loads or poor installation practice for which higher pipe stiffness may be required to minimize deflection of the installed pipes.

Stiffness class SN1.5 in sizes greater than DN 100 has been included to accommodate pipes currently manufactured and shown to perform satisfactorily.

NOTE: This Standard no longer includes ribbed profile-wall pipes, (formed from a profile with a seam), in diameters DN 375–DN 1050.

Pipe stiffness is a measure of resistance of a pipe to ring deflection and is determined by testing or calculation, in newtons per metre per metre length.

Users wishing to compare the stiffness of pipes made to the previous classification scheme (AS 1254—1981 and NZS 7649—1988), with current requirements may use the equation of Clause 1.3.11.

The E_b value for sandwich construction pipe may be less than that for plain wall pipe of the same wall thickness. To achieve the same pipe stiffness, a sandwich construction pipe might require a greater wall thickness than for an equivalent plain wall pipe.

Caution is advised, however, because it is necessary to assume a value of the initial three-minute ring bending modulus E_b of PVC in the equation. The committee has assumed a value of 3 200 MPa for PVC (as recommended in AS/NZS 2566.1) for the three-minute ring bending modulus (E_b). This value is not a 'material constant'; it depends on the resin used, and the influence of the additives and fillers used in the manufacture of PVC stormwater pipes. While calculations are useful for estimating pipe stiffness and wall thickness, these values should only be used as guidelines.

The term 'informative' has been used in this Standard to define the application of the appendix to which it applies. An 'informative' appendix is only for information and guidance.

The test criteria of this Standard apply to pipes and fittings at the time of manufacture and should not be used to assess the results from tests on pipes or fittings which have been in service.

Any fitting already marked in accordance with the superseded Standards listed above will be considered acceptable and complying with the marking requirements of this Standard (Clause 5.6) for a period of three years from the date of publication of the Standard.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-