

AS 2473—1996

Australian Standard®

**Valves for compressed gas
cylinders (threaded outlet)**

This Australian Standard was prepared by Committee ME/2, Gas Cylinders. It was approved on behalf of the Council of Standards Australia on 14 June 1996 and published on 5 October 1996.

The following interests are represented on Committee ME/2:

Australian Chamber of Commerce and Industry
Australian Chamber of Manufactures
Australian Gas Association
Australian Liquefied Petroleum Gas Association
Boiler and Pressure Vessel Manufacturers Association
Department of Defence
Department of Industrial Affairs, S.A.
Department of Labour, New Zealand
Department of Minerals and Energy, Qld
Department of Training and Industrial Relations, Qld
Fire Protection Industry Association of Australia
Health and Safety Organisation, Vic.
Institute of Metals and Materials Australasia
Insurance Council of Australia
Tasmania Development and Resources
Telarc New Zealand
Welding Technology Institute of Australia
WorkCover Authority, A.C.T.
WorkCover Authority, N.S.W.
WorkCover Authority, N.T.
WorkSafe and Welfare, W.A.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 95102.

AS 2473—1996

Australian Standard[®]

**Valves for compressed gas
cylinders (threaded outlet)**

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7337 0675 4

PREFACE

This Standard was prepared by the Standards Australia/Standards New Zealand Committee ME/2 on Gas Cylinders to supersede AS 2473—1990. It is the result of a consensus among representatives on the Joint Committee to produce it as an Australian Standard.

This Standard introduces a number of new connections which fully differentiate valve outlets by gas and maximum filling pressure. It also makes minor changes to the figures in Appendix B to correct previous errors in the metrication carried out in the 1981 edition.

Also in this Standard is the introduction of a program of conversion of certain types of gas outlets. The conversion concerns compressed air and inert gases (including shielding gases) and the details are given in Clause 12 of this Standard.

Formerly, Type 10 was specified for oxygen, air and the permanent inert gases for filling pressures up to 20 000 kPa (200 bar) at 15°C. Type 11 connection was specified for oxygen, air and the inert permanent gases with a filling pressures above 20 000 kPa (200 bar) at 15°C.

In this edition, connections from ISO 5154 are introduced for air and permanent inert gases for filling pressures up to 20 000 kPa (200 bar) at 15°C. Connections from CGA V-1 are used with minor adjustments to the cut-off pressures. This change allows specific oxygen-only connections. The existing Type 10 connection is retained for use at up to 17 500 kPa (175 bar) at 15°C. A new Type 10.5 connection is introduced for use at up to 20 000 kPa (200 bar) at 15°C. The existing Type 11 connection is retained for use at up to 25 000 kPa (250 bar) at 15°C and a new Type 16 connection (similar to Connection 701 from ANSI/GGA V-1) is introduced for service at up to 31 500 kPa (315 bar) at 15°C. For air, inert gases and high-pressure flammable gases, connections are introduced for filling pressures up to 31 500 kPa (315 bar) and up to 42 500 kPa (425 bar), both pressures being at 15°C.

Additionally, outlet details for gases not specifically listed have been revised, including new connections from BS 341 for use with small cylinders.

The term 'normative' has been used in this Standard to define the application of the appendix to which it applies. A 'normative' appendix is an integral part of a Standard.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	5
4 THREADS	5
5 DIMENSIONS	5
6 VALVE OPERATION	6
7 MATERIALS	6
8 MANUFACTURE	6
9 PRESSURE RATING	6
10 TESTING	6
11 MARKING	7
12 PROGRAM FOR AIR AND INERT GAS OUTLET CONVERSION	7

APPENDICES

A WHERE A $\frac{3}{8}$ -INCH BSP PARALLEL THREAD CYLINDER VALVE WITH A SOFT-SOLDERED SEAL MAY BE USED	55
B RECOMMENDED GAUGES FOR CYLINDER NECK AND VALVE STEM THREADS	57
C SUGGESTED SAMPLE SELECTION FOR TEST PURPOSES	63
D IMPACT STRENGTH TEST FOR VALVES/VALVE PROTECTION	64

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-