



## **Road tank vehicles for dangerous goods**

### **Part 4: Tankers for toxic and corrosive cargoes**



This Australian Standard® was prepared by Committee ME-057, Road Tankers for Hazardous Liquids and Gases. It was approved on behalf of the Council of Standards Australia on 13 March 2017.

This Standard was published on 26 April 2017.

---

The following are represented on Committee ME-057:

- Australasian Fire and Emergency Service Authorities Council
  - Australia New Zealand Industrial Gas Association
  - Australian Chamber of Commerce and Industry
  - Australian Industry Group
  - Australian Institute of Petroleum Gas
  - Energy Australia
  - National Bulk Tanker Association
  - National Heavy Vehicle Regulator
  - Petroleum Industry Contractors Association
  - Queensland Transport
  - SafeWork SA
  - The Bitumen Users Group
  - WorkSafe Victoria
- 

This Standard was issued in draft form for comment as DR AS 2809.4:2016.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

---

### **Keeping Standards up-to-date**

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting [www.standards.org.au](http://www.standards.org.au)

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.org.au](mailto:mail@standards.org.au), or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

Australian Standard®

## Road tank vehicles for dangerous goods

### Part 4: Tankers for toxic and corrosive cargoes

Originated as AS 2809.4—1986.  
Previous edition 2001.  
Third edition AS 2809.4:2017.

#### **COPYRIGHT**

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 76035 732 0

## PREFACE

This Standard was prepared by the Standards Australia Committee ME-057, Road Tankers for Hazardous Liquids and Gases, to supersede AS 2809.4—2001. It is complementary to AS 2809.1—1999, *Road tank vehicles for dangerous goods*, Part 1: *General requirements*, and provides requirements that are specifically applicable to road tankers for the transport of liquids that are toxic or corrosive or both.

Please note that the scope of this revision was limited; a further revision of the full AS 2809 series, including this Standard, has been approved by Standards Australia and is currently underway.

This Standard is Part 4 of the AS 2809 series, which comprises six Parts. Part 1 specifies general requirements for all road tank vehicles and Parts 2 to 6 provide specific requirements applicable to particular road tank vehicles. The series is as follows:

### AS

|        |   |
|--------|---|
| 2809   | Road tank vehicles for dangerous goods                          |
| 2809.1 | Part 1: General requirements for all road tank vehicles         |
| 2809.2 | Part 2: Road tank vehicles for flammable liquids                |
| 2809.3 | Part 3: Road tank vehicles for compressed liquefied gases       |
| 2809.4 | Part 4: Tankers for toxic and corrosive cargoes (this Standard) |
| 2809.5 | Part 5: Tankers for bitumen-based products                      |
| 2809.6 | Part 6: Tankers for cryogenic liquids                           |

This Standard was written at the request of state statutory authorities for the purpose of providing a reference standard for state regulations dealing with safety in the transport of dangerous goods. Since no other national standards existed from which requirements could be derived, this Standard has been modelled largely as dictated by industry experience in the transport of these goods.

This Standard deals with all the substances covered by Classes 6 and 8 of *The Australian Dangerous Goods Code* (ADG Code), although it is recognized that only a small number of them are transported in such a volume that specific road tankers are built to deal with them. For such materials, transport is by conventional trucks using packages or container tanks.

Specific attention is drawn to the following features of this Standard:

- (a) A variety of types of tanks are provided for, according to the characteristics of the cargo. For certain very highly toxic substances, two needs are paramount, i.e. venting must be severely restricted, and the tank must be unusually robust to prevent splitting or tearing in the event of collision or rollover. For this class of cargo, the cargo tank is a pressure vessel, and specific design pressures are nominated, which vary according to the grade of toxicity and the normal vapour pressure. At lower levels of toxicity, a pressure vessel is only required if the normal vapour pressure requires it; otherwise cargo density is the only parameter. For corrosive cargo, the density, the vapour pressure, and the tank life are the main parameters.

To facilitate the selection of the correct type of tank for the particular cargo, the ADG Code incorporates an addition to its 'Packaging Method' code, indicating the type of tanker to be used if transport is in bulk. This Standard prescribes the construction of each type of tank.

- (b) Additional shell thicknesses for corrosive cargo are not specifically nominated. The approach is that the corrosion allowance needs to be worked out for the particular characteristics of the cargo, from known attack rates, and for a predetermined tank life, for which 8 years is recommended; however, it is recognized that short-life tanks may have occasional applications, so appropriate judgement provisions are included.

- (c) Any opening into the tank, e.g. vents, hatches and filling provisions, present particular problems for these classes of cargo. It is desirable to protect the tank against excessive pressure accumulations arising either from environmental or chemical causes, especially in the aftermath of an accident. However, the conventional spring-loaded pressure, vacuum, and emergency vents usual in petroleum service are not always suitable. They are vulnerable to fouling by corrosives, and toxic materials generally cannot be allowed to vent.

Hatches for filling, and manhole openings for entry for cleaning or inspection, present similar problems, i.e. there is a greater need for cargo retention after an accident.

Clauses of this Standard relating to vents represent an attempt to give general guidance on this complex and difficult matter, as Committee ME-057 considers it to be impracticable to treat the individual needs of each dangerous substance. Specific agreements between the owner, the manufacturer, and the authority will often be necessary.

**IT SHOULD BE NOTED THAT COMPLIANCE WITH THIS STANDARD MAY NOT NECESSARILY FULFIL ALL THE LEGAL OBLIGATIONS.**

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
  - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-