This is a free page sample. Access the full version online.

National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 1762:2003

ICS 23.040.70

National Standards
Authority of Ireland
Dublin 9
Ireland

Tel: (01) 807 3800
Tel: (01) 807 3838

RUBBER HOSES AND HOSE ASSEMBLIES FOR LIQUEFIED PETROLEUM GAS, LPG (LIQUID OR GASEOUS PHASE), AND NATURAL GAS UP TO 25 BAR (2,5 MPA) - SPECIFICATION

This Irish Standard was published under the authority of the National Standards Authority of Ireland and comes into effect on:

November 28, 2003

NO COPYING WITHOUT NSAI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

© NSAI 2003

Price Code F

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

This is a free page sample. Access the full version online.

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 1762:2003/AC

November 2007
Novembre 2007
November 2007

ICS 23.040.70

English version
Version Française
Deutsche Fassung

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specification

Tuyaux et flexibles en caoutchouc pour le gaz de pétrole liquéfié GPL (en phase liquide ou gazeuse) et le gaz naturel jusqu'à 25 bar (2,5 MPa) - Spécification

Gummischläuche und -schlauchleitungen für Flüssiggas LPG (flüssig oder gasförmig) und Erdgas bis 25 bar (2,5 MPa) - Spezifikation

This corrigendum becomes effective on 28 November 2007 for incorporation in the three official language versions of the EN.

Ce corrigendum prendra effet le 28 novembre 2007 pour incorporation dans les trois versions linguistiques officielles de la EN.

Die Berichtigung tritt am 28.November 2007 zur Einarbeitung in die drei offiziellen Sprachfassungen der EN in Kraft.

EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

© 2007 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.
Tous droits d'exploitation sous quelque forme et de quelque manière que ce soit réservés dans le monde entier aux membres nationaux du CEN.
Alle Rechte der Verwertung, gleich in welcher Form und in welchem Verfahren, sind weltweit den nationalen Mitgliedern von CEN vorbehalten.

Ref. No.:EN 1762:2003/AC:2007 D/E/F

This is a free page sample. Access the full version online.

English version

In Table 3 "Physical properties of compounds" the layout of row 6 has to be changed because in the present version it is not clear, whether variation of hardness, max. hardness value after aging and max. mass reduction are to be measured after additional drying or whether variation of hardness and max. hardness value after aging are to be measured directly after storing in n-pentane.

In Table 3, replace row 6 with the following 2 rows:

5.1 Immersion in n-pentane Max. mass increase	%	10	-	ISO 1817 7 days storing in n-pentane at +23 °C
5.2 Drying after immersion Variation of hardness Max. hardness value Max. mass reduction	 IRHD IRHD %	 +10/-3 85 -5 -10 (LT-Types)	 - -	ISO 1817 drying for 70 h at + 40 °C

Version française

Dans le Tableau 3 "Caractéristiques physiques des mélanges" la disposition de la ligne 6 doit être modifiée car la version actuelle n'est pas claire, si la variation de dureté, la valeur maximale de dureté après vieillissement et la réduction maximale de masse doivent être mesurées après séchage supplémentaire ou si la variation de dureté et la valeur maximale de dureté après vieillissement doivent être mesurés directement après stockage dans du n-pentane.

Dans le Tableau 3, remplacer la ligne 6 par les 2 lignes suivantes :

5.1 Immersion dans du n-pentane Augmentation de masse, max	%	10	-	ISO 1817 7 jours de stockage dans du n-pentane à +23 °C
5.2 Séchage après immersion Variation de dureté valeur de dureté réduction de masse, max	 DIDC DIDC %	 +10/-3 85 -5 -10 (types LT-)	 - -	ISO 1817 séchage pendant 70 h à + 40 °C

This is a free page sample. Access the full version online.

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 1762

October 2003

ICS 23.040.70

Supersedes EN 1762:1997

English version

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specification

Tuyaux et flexibles en caoutchouc pour le gaz de pétrole liquéfié GPL (en phase liquide ou gazeuse) et le gaz naturel jusqu'à 25 bar (2,5 MPa) - Spécification

Gummischläuche und -schlauchleitungen für Flüssiggas LPG (flüssig oder gasförmig) und Erdgas bis 25 bar (2,5 MPa) - Spezifikation

This European Standard was approved by CEN on 8 September 2003.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Slovakia, Spain, Sweden, Switzerland and United Kingdom.

EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

© 2003 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN 1762:2003 E

This is a free page sample. Access the full version online.

Contents

Page

Foreword 3

1 Scope 3

2 Normative references 3

3 Terms and definitions 4
3.1 Additional Terms and definitions 4
3.1.1 Electrically Bonded Hose/Hose Assembly 4
3.1.2 Electrically Conductive Hose/Hose Assembly 4
3.1.3 Electrically Discontinuous Hose/Hose Assembly 4

4 Classification 4

5 Materials and construction 5
5.1 Hose 5
5.2 Hose assemblies 5

6 Dimensions 5
6.1 Nominal bore, internal diameters, outside diameters, tolerances, and minimum bend radius 5
6.2 Minimum thickness of lining and cover 7
6.3 Concentricity 7
6.4 Tolerances on length 7

7 Physical properties 7
7.1 Rubber Compounds 7
7.2 Finished hose & hose assemblies 7

8 Electrical properties 9
8.1 Textile reinforced hoses with bonding wires. 9
8.2 Textile reinforced hoses with conducting materials. 9
8.3 Wire helix reinforced hoses 9
8.4 Hose assemblies that are required to be discontinuous 9

9 Type approval 9

10 Frequency of testing 9

11 Marking 10
11.1 Hoses 10
11.2 Hose assemblies 10

Annex A (normative) Flammability test 11
A.1 Method 11
A.2 Assessment 11

Annex B (normative) **Test frequency** 12

Annex C (informative) **Test frequency** 13

SAI GLOBAL

This is a free preview. Purchase the entire publication at the link below:

Product Page

Looking for additional Standards? Visit Intertek Inform Infostore

Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation