This is a free page sample. Access the full version online.

National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 2647:2006

ICS 49.030.30

AEROSPACE SERIES - NUTS, HEXAGONAL, SELF-LOCKING, BALL SEAT, IN ALLOY STEEL, CADMIUM PLATED, MOS2 LUBRICATED - CLASSIFICATION: 900 MPA (AT AMBIENT TEMPERATURE)/235 °C

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
http://www.nsai.ie

Sales
http://www.standards.ie

This Irish Standard was published under the authority of the National Standards Authority of Ireland and comes into effect on:

10 August 2006

NO COPYING WITHOUT NSAI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

© **NSAI 2006**

Price Code E

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

This is a free page sample. Access the full version online.

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 2647

June 2006

ICS 49.030.30

Supersedes EN 2647:1995

English Version

Aerospace series - Nuts, hexagonal, self-locking, ball seat, in alloy steel, cadmium plated, MoS2 lubricated - Classification: 900 MPa (at ambient temperature)/235 °C

Série aérospatiale - Écrous hexagonaux, à freinage interne, orientables, en acier allié, cadmiés, lubrifiés MoS2 - Classification: 900 MPa (à température ambiante)/235 °C

Luft- und Raumfahrt - Sechskantmuttern, selbstsichernd, für Neigungsausgleich, aus legiertem Stahl, verkadmet, MoS2-geschmiert - Klasse: 900 MPa (bei Raumtemperatur)/235 °C

This European Standard was approved by CEN on 3 February 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

© 2006 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. EN 2647:2006: E

This is a free page sample. Access the full version online.

Contents

Page

Foreword 3
1 Scope 4
2 Normative references 4
3 Required characteristics 5
4 Designation 7
5 Marking 7
6 Technical specification 7
Annex A (informative) Assembly 8

This is a free page sample. Access the full version online.

Foreword

This European Standard (EN 2647:2006) has been prepared by the AeroSpace and Defense Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by December 2006, and conflicting national standards shall be withdrawn at the latest by December 2006.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

This document supersedes EN 2647:1995.

This is a free page sample. Access the full version online.

1 Scope

This standard specifies the characteristics of self-locking hexagonal nuts with ball seat in alloy steel, cadmium plated, MoS_2 lubricated.

Classification: 900 MPa[1)] / 235 °C[2)]

They are intended to be used with washers to EN 2648 or suitable parts, see Annex A.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5855-2, *Aerospace — MJ threads — Part 2: Limit dimensions for bolts and nuts*

ISO 5858, *Aerospace — Self-locking nuts with maximum operating temperature ≤ 425 °C — Procurement specification*

ISO 8788, *Aerospace — Nuts, metric — Tolerances of form and position*

EN 2000, *Aerospace series — Quality assurance — EN aerospace products — Approval of the quality system of manufacturers*

EN 2133, *Aerospace series — Cadmium plating of steels, with maximum specified tensile strength ≤ 1 450 MPa, copper, copper alloys and nickel alloys*

EN 2424, *Aerospace series — Marking of aerospace products*

EN 2491, *Aerospace series — Molybdenum disulphide dry lubricants — Coating methods*

EN 2648, *Aerospace series — Washers, concave, in alloy steel, cadmium plated*

EN 9133, *Aerospace series — Quality management systems — Qualification procedure for aerospace standard parts*

TR 3791, *Aerospace series — Materials for all metal self-locking nuts and thin wall inserts of temperature classes ≤ 425 °C*[3)]

---

1) Corresponds to the minimum tensile stress which the nut is able to withstand at ambient temperature without breaking or cracking when tested with a bolt of a higher strength class.

2) Maximum temperature that the nut is able to withstand, without permanent alteration to is original characteristics, after ambient temperature has been restored. The maximum temperature is conditioned by the cadmium plating.

3) Published as AECMA Technical Report at the date of publication of this standard

SAI GLOBAL

This is a free preview. Purchase the entire publication at the link below:

Product Page

Looking for additional Standards? Visit Intertek Inform Infostore

Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation