



National Standards Authority of Ireland

STANDARD

I.C.P. 3 : 1989

ICS 91.140.40

National Standards  
Authority of Ireland  
Dublin 9  
Ireland

Tel: (01) 807 3800  
Fax: (01) 807 3838

**DOMESTIC INSTALLATIONS FOR  
MANUFACTURED AND NATURAL GAS  
(EDITION 2)**

*This Irish Standard was  
published under the  
authority of the National  
Standards Authority of  
Ireland  
and comes into effect on:  
May 5, 1989*

**NO COPYING WITHOUT NSAI  
PERMISSION EXCEPT AS  
PERMITTED BY COPYRIGHT  
LAW**

© NSAI 1989

**Price Code W**

Údarás um Chaighdeán Náisiúnta na hÉireann





National Standards Authority of Ireland

AMENDMENT

I.C.P. 3 : 1989 : Amd 4 : 1992

ICS 91.140.40

National Standards  
Authority of Ireland  
Dublin 9  
Ireland

Tel: (01) 807 3800  
Fax: (01) 807 3838

**DOMESTIC INSTALLATIONS FOR  
MANUFACTURED AND NATURAL GAS  
(EDITION 2)**

*This Irish Standard was  
published under the  
authority of the National  
Standards Authority of  
Ireland  
and comes into effect on:  
August 4, 1992*

**NO COPYING WITHOUT NSAI  
PERMISSION EXCEPT AS  
PERMITTED BY COPYRIGHT  
LAW**

© NSAI 1992

**Price Code B**

Údarás um Chaighdeáin Náisiúnta na hÉireann



GTSC.TC2.269.92  
February 1992

NATIONAL STANDARDS AUTHORITY OF IRELAND

Gas Technical Standards Committee

DRAFT AMENDMENT NO. 4 TO ICP 3

(DOMESTIC INSTALLATIONS USING NATURAL GAS)

6.3.5 SPECIFIC REQUIREMENTS FOR THE INSTALLATION OF DECORATIVE AND  
INSET LIVE FUEL EFFECT FIRES

6.3.5.1 The definition of Decorative and Inset Live Fuel Effect Fires are included in the Definition Section. For illustrations - see Appendix 5.

6.3.5.2 Flue Requirements:

Before fixing any open flued fire covered by this standard, correct operating of the flue shall be verified in accordance with Section 3.

For decorative fuel effect fires ensure that the flue serving the appliance shall have no cross-sectional dimension less than 175 mm.

For inset live fuel effect fires the cross-sectional area of the flue shall not be less than the cross-sectional area of the appliance flue outlet.

6.3.5.3 Location of Burner Tray:

When a decorative fuel effect fire is fitted into a fireplace, the front edge of the burner tray must not protrude beyond the front edge of the fireplace opening (see Figure 5 (i) of Appendix 5).

Hearth requirements are to be in accordance with Section 6.

The appliance shall be securely fixed to the hearth and assembled in accordance with the manufacturers instructions. It is imperative that the manufacturers instructions with regard to assembly of all the components (coals, matrix, ceramics etc.) should be strictly observed.



This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- Looking for additional Standards? Visit Intertek Inform Infostore
  - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-